



i • RETROFIT

IR-RTROC-360-XXW

# LED RETROFIT 360° CORN LIGHT 12W - 75W

- Vertical Installation
- Ballast Compatible
- IP65



(\*only for E39 base)



i • RETROFIT

# LED RETROFIT 360° CORN LIGHT 12W - 75W, BALLAST COMPATIBLE, IP65

IR-RTROC-360-XXW



**12W**

**16W**

**20W**

**24W**

**28W**




Replaces



## Ø3" Internal Driver 360° Corn Lamp

Part Number	Watt	Lumens(±10%)	LED QTY	PF	CRI	Voltage	CCT	IP Rating	Base Type
IR-RTROC-360-12W	12W	1320lm	40pcs Samsung 2835 Epistar 2835	>0.9	>80	100-300VAC	3,000, 4,000 5,000	IP65	E26/E39
IR-RTROC-360-16W	16W	1760lm	50pcs Samsung 2835 Epistar 2835	>0.9	>80	100-300VAC	3,000, 4,000 5,000	IP65	E26/E39
IR-RTROC-360-20W	20W	2200lm	60pcs Samsung 2835 Epistar 2835	>0.9	>80	100-300VAC	3,000, 4,000 5,000	IP65	E26/E39
IR-RTROC-360-24W	24W	2460lm	80pcs Samsung 2835 Epistar 2835	>0.9	>80	100-300VAC	3,000, 4,000 5,000	IP65	E26/E39
IR-RTROC-360-28W	28W	3080lm	90pcs Samsung 2835 Epistar 2835	>0.9	>80	100-300VAC	3,000, 4,000 5,000	IP65	E26/E39





i • RETROFIT

# LED RETROFIT 360° CORN LIGHT 12W - 75W, BALLAST COMPATIBLE, IP65

IR-RTROC-360-XXW



Replaces



## Ø3.5" Internal Driver 360° Corn Lamp

Part Number	Watt	Lumens(±10%)	LED QTY	PF	CRI	Voltage	CCT	IP Rating	Base Type
IR-RTROC-360-27W	27W	2970lm	90pcs Samsung 2835 Epistar 2835	>0.9	>80	100-300VAC	3,000, 4,000 5,000	IP65	E26/E39
IR-RTROC-360-36W	36W	3960lm	120pcs Samsung 2835 Epistar 2835	>0.9	>80	100-300VAC	3,000, 4,000 5,000	IP65	E26/E39
IR-RTROC-360-45W	45W	4950lm	150pcs Samsung 2835 Epistar 2835	>0.9	>80	100-300VAC	3,000, 4,000 5,000	IP65	E26/E39
IR-RTROC-360-54W	54W	5940lm	180pcs Samsung 2835 Epistar 2835	>0.9	>80	100-300VAC	3,000, 4,000 5,000	IP65	E26/E39
IR-RTROC-360-75W	75W	8250lm	252pcs Samsung 2835 Epistar 2835	>0.9	>80	100-300VAC	3,000, 4,000 5,000	IP65	E26/E39



(\*only for E39 base)





i • RETROFIT

# LED RETROFIT 360° CORN LIGHT 12W - 75W, BALLAST COMPATIBLE, IP65

IR-RTROC-360-XXW



## Samsung & Epistar Chip

High lumen flux, 120lm/w  
LM-80 Listed



Ø 3"



Ø 3.5"



## 6063 Aluminum

6063 Aluminum thermal structure  
High Quality aluminum processing technique  
Special Surface treatment process



## Driver

Rubycon capacitors  
Compatible with most exiting ballasts

## Features

- Compatible with existing ballasts.
- Suitable for use in enclosed luminaires
- **IP65 ingress protection**
- Replacement for HID, MHL high bay or post top applications
- E26/E39 socket adapter available
- AC100-300V input range
- Samsung 2835 series (Epistar 2835 optional)
- Independent developed driver with Rubycon capacitor
- Dow Corning RTV-T thermal silicone
- UL (E472642), LM80 listed Certification
- 5 Years Warranty

